

WP Series Grade 2 Lever



Enhance Convenience of Keyless Entry

Access your way – with mobile credentials, access cards, fobs, and/or pin codes.

Improve Security

Eliminate risk & costs of lost & duplicated keys, while gaining visibility & control of Access Events.

Change the Game with Mobile Credentials

Unlimited mobile credentials that can be issued or revoked from anywhere with access software.

Affordable, Simple Installation

Direct to Wi-Fi connectivity simplifies installation, eliminating costly wire runs and the complexity and cost of gateways and hubs.

Manage it Remotely

Offers the convenience of connecting to cloud-based software to manage and monitor your facility's access needs from anywhere.

Enhanced Battery Life

Patented 'heartbeat interval' allows configurable updates & extends battery life up to 2+ years, plus low battery warnings.

Architectural Finishes



626 (US26D)
Satin Chromium
(Default)



606 (US4)
Satin Brass



613E
Dark Oxidized Satin
Bronze (Equivalent)



622 (US19)
Flat Black

Cylinders



Conventional, Restricted,
High Security, SFIC

Levers



Philadelphia - PHL
(Default)



Boston - BSN



Miami - MIA

Key Features

Reliable & Secure

- Our Go-To Commercial Lock
- Meets most commercial needs
- Interior or Exterior Usage
- Commercial-Grade 2 Cylindrical
- UL 20 min fire rating

Convenient Credential Options

- Mobile, card, fob, pin code
- Key backup

Remote Management & Notifications

With access software

Uninterrupted Door-Access

Stores programming in case of power outage or offline network

Easy Installation

- No-drilling on standard door preps
- For 2 3/8" and 2 3/4" door backsets

Commercial – Custom Keying

Match existing keying systems, add high security options, or convenience of Keyed Alike.

Specifications

Installation	For 2 3/8" and 2 3/4" door backsets without further drilling	
Bore Diameter	2 1/8"	
Backset	Adj 2 3/8" & 2 3/4"	
Door Thickness	1 3/8" to 1 3/4" thick	
Handing	Available pre-handed (LH or RH), Field reversible in 5 minutes	
Credentials	Pin Code, Fob/Card (Mifare 13.56 MHz), Mobile Credentials, Key Backup	
Keyways	Conventional, Keyed Alike, SFIC, Restricted, High Security, UL437	
Access Events	Up to 4,000 events stored on device when offline, up to 365 days with cloud access software.	
Schedules	Up to 28 Lock (device) Schedules (e.g. auto-unlock M 8am, lock M 5pm) Up to 40 User Access Schedules (e.g. M-F 9-5) Up to 20 Access Exception Schedules (e.g. Holidays, Shutdowns)	
Audible	Audible indicator of key press, configurable	
Visual	Keypad backlit upon key press	
Batteries	(4) AA Alkaline batteries, Battery life based on usage conditions, up to 2+ years	
Connectivity Options	Direct to Bluetooth via mobile device (send updates at the lock) Direct to Wi-Fi via wireless access point with internet connection (up to every 15 minutes)	
BLE Communication	Bluetooth® Low Energy (BLE) v4.2, v5.2	
Wi-Fi Communication	2.4 GHz Wi-Fi (IEEE 802.11 b/g/n) Security: WEP, WPA, WPA2, and WPA3 supported	Port: 443
Encryption	Advanced Encryption Standard (AES), 256-bit Transport Layer Security (TLS) version 1.2	
Operating Environment	-20° to 65°C, 0-95% Humidity (non-condensing)	
Fire Rating (UL/CUL 10C)	UL/CUL 10C 20-Minutes	
Certifications	ADA Compliant (Americans with Disabilities Act) ANSI/BHMA A156.2 Grade 2 Cylindrical Lock	FCC Part 15
Warranty	2-year Hardware, 1-year Electronics	
COO	Designed & Assembled in USA	

Ready to Ship TrueSecure Wi-Fi Grade 2 Lever Lock WP Series

ITEM#	TrueSecure "WP" Wi-Fi Grade 2 Lever Commercial Smart Wi-Fi Lock Mifare, Keypad, BLE w/Mobile		
TS-WPG2-MKB-622-LH	Black Finish Left Handed	TS-WPG2-MKB-626-LH	Silver Finish Left Handed
TS-WPG2-MKB-622-RH	Black Finish Right Handed	TS-WPG2-MKB-626-RH	Silver Finish Right Handed

How to Order



	CODE
Brand	TS = TruSecure
Series	WP
Latch	G2 = Two Cylindrical Included: 2 3/8" & 2 3/4"
Credential	M = Mifare, K = Keypad, B = BLE w/Mobile
Lever	PHL = Philidelphia (default)
Finish	622 = Flat Black (US19) 626 = Satin Chromium (US26D)
Handing	RH = Right Handing, LH = Left Handing
Backset	2 3/8" or 2 3/4"
Strike	Two Included: ASA & T
Cylinder	SCC = Schlage 6-pin, 5-bit key
Keyway	C = Schlage 'C' Keyway
Keying	KD = Keyed Different (default)

SPECIAL ORDER	CODE
Lever	BSN = Boston, MIA = Miami
Finish	613 = Dark Oxidized Satin Bronze 606 = Satin Brass (US4)
Backset	5"
Strike	FL = Full Lip 1 5/8" x 2 1/4"
Cylinder	SFIC = Small format IC Core Restricted = Restricted Formats UL437 = High Security Cores L = Less Cylinder SFL = SFIC Less Core
Keyway	15+ Keyways
Keying	KA = Keyed Alike KE = Keyed to Existing KO = Zero Blttd MK = Master Key