

# WP Series Interconnected



## Enhance Convenience of Keyless Entry

Access your way – with mobile credentials, access cards, fobs, and/or pin codes.

## Improve Security

Eliminate risk & costs of lost & duplicated keys, while gaining visibility & control of Access Events.

## Change the Game with Mobile Credentials

Unlimited mobile credentials that can be issued or revoked from anywhere with access software.

## Affordable, Simple Installation

Direct to Wi-Fi connectivity simplifies installation, eliminating costly wire runs and the complexity and cost of gateways and hubs.

## Manage it Remotely

Offers the convenience of connecting to cloud-based software to manage and monitor your facility's access needs from anywhere.

## Enhanced Battery Life

Patented 'heartbeat interval' allows configurable updates & extends battery life up to 2+ years, plus low battery warnings.

## Architectural Finishes



626 (US26D)  
Satin Chromium  
(Default)



606 (US4)  
Satin Brass



613E  
Dark Oxidized Satin  
Bronze (Equivalent)



622 (US19)  
Flat Black

## Cylinders



Conventional, Restricted,  
High Security, SFIC

## Levers



Philadelphia - PHL  
(Default)



Boston - BSN



Miami - MIA

## Key Features

### Reliable & Secure

- Commercial-Grade, Interconnected Lock
- UL 20 min fire rating
- 2-year mechanical warranty

### Convenient Credential Options

- Mobile, card, fob, pin code
- Key backup

### Remote Management & Notifications

With access software

### Uninterrupted Door-Access

Stores programming in case of power outage or offline network

### Easy Installation

- Designed for quick installation
- Door backset: 2 3/8" or 2 3/4"
- Door thickness: 1 3/8" to 1 3/4"

### Commercial – Custom Keying

Match existing keying systems, add high security options, or convenience of Keyed Alike.

## Specifications

Bore Diameter	2 1/8"	
Backset	Adj 2 3/8" and 2 3/4"	
Door Thickness	1 3/8" to 1 3/4" thick	
Handing	Non-handed ('pin' field reversible)	
Credentials	Pin Code, Fob/Card (Mifare 13.56 MHz), Mobile Credentials, Key Backup	
Keyways	Conventional, Keyed Alike, SFIC, Restricted, High Security, UL437	
Access Events	Up to 4,000 events stored on device when offline, up to 365 days with cloud access software.	
Schedules	Up to 28 Lock (device) Schedules (e.g. auto-unlock M 8am, lock M 5pm) Up to 40 User Access Schedules (e.g. M-F 9-5) Up to 20 Access Exception Schedules (e.g. Holidays, Shutdowns)	
Audible	Audible indicator of key press, configurable	
Visual	Keypad backlit upon key press	
Batteries	(4) AA Alkaline batteries, Battery life based on usage conditions, up to 2+ years	
Connectivity Options	Direct to Bluetooth via mobile device (send updates at the lock) Direct to Wi-Fi via wireless access point with internet connection (up to every 15 minutes)	
BLE Communication	Bluetooth® Low Energy (BLE) v4.2, v5.2	
Wi-Fi Communication	2.4 GHz Wi-Fi (IEEE 802.11 b/g/n) Security: WEP, WPA, WPA2, and WPA3 supported	Port: 443
Encryption	Advanced Encryption Standard (AES), 256-bit, Transport Layer Security (TLS) version 1.2	
Operating Environment	-20° to 65°C, 0-95% Humidity (non-condensing)	
Fire Rating (UL/CUL 10C)	UL/CUL 10C 20-Minutes	
Certifications	ADA Compliant (Americans with Disabilities Act), FCC Part 15	
Warranty	2-year Hardware, 1-year Electronics	
COO	Designed & Assembled in USA	

## Ready to Ship TrueSecure Wi-Fi Interconnected Lever Lock WP Series

ITEM#	TrueSecure "WP" Interconnected   Commercial Smart Wi-Fi Lock   Mifare, Keypad, BLE w Mobile
TS-WPIN-MKB-622	Black Finish
TS-WPIN-MKB-626	Silver Finish

## How to Order



	CODE
Brand	<b>TS</b> = TruSecure
Series	<b>WP</b>
Latch	<b>IN</b> = Interconnected
Credential	<b>M</b> = Mifare, <b>K</b> = Keypad, <b>B</b> = BLE w/Mobile
Lever	<b>PHL</b> = Philidelphia (default)
Finish	<b>622</b> = Flat Black (US19) <b>626</b> = Satin Chromium (US26D)
Handing	Field reversible
Backset	<b>Adj:</b> 2 3/8" & 2 3/4"
Strike	ASA (default) 1 1/4" x 4 7/8"
Cylinder	<b>SCC</b> = Schlage 6-pin, 5-bit key
Keyway	<b>C</b> = Schlage 'C' Keyway
Keying	<b>KD</b> = Keyed Different (default)

SPECIAL ORDER	CODE
Lever	<b>BSN</b> = Boston, <b>MIA</b> = Miami
Finish	<b>613</b> = Dark Oxidized Satin Bronze <b>606</b> = Satin Brass (US4)
Strike	<b>T</b> = T-Strike 1 1/8" x 2 3/4" <b>FL</b> = Full Lip 1 5/8" x 2 1/4"
Cylinder	<b>SFIC</b> = Small format IC Core <b>Restricted</b> = Restricted Formats <b>UL437</b> = High Security Cores <b>L</b> = Less Cylinder <b>SFL</b> = SFIC Less Core
Keyway	15+ Keyways
Keying	<b>KA</b> = Keyed Alike <b>KE</b> = Keyed to Existing <b>KO</b> = Zero Blttd <b>MK</b> = Master Key